

Response	Type	Length (mm)	RTI**		Strength				Temperature							Comp. Listed	
			Response Time Index		Average Crush Load		LTL		Additional temperatures available								
			(ms) ^{1/2}	(fts) ^{1/2}	kN	lbs	kN	lbs	57°C	68°C	79°C	93°C	141°C	182°C	260°C		
										135°F orange	155°F red	175°F yellow	200°F green	286°F blue	360°F mauve	500°F black	
Standard	G5	16 / 20	90	163	4,0	880	2,5	550									UL, LPCB, VdS
	G5-XS	16 / 20	90	163	5,5	1210	4,0	880									
Intermediate	F5	16 / 20	68	123	4,0	880	2,5	550									TFRI
	F4	16 / 20	58	105	4,0	880	2,5	550									
Fast	F3-SP	20	32	58	4,1	900	2,3	500									UL, LPCB
	F3	16 / 20	32	58	3,5	770	2,0	440									UL, LPC, TFRI
	F3-XS	16 / 20	32	58	4,5	990	3,0	660									
	F3-F	16 / 20	24	43	4,1	900	2,3	500									UL*
Super Fast	F2.5	16 / 20	24	43	2,5	550	1,25	275									UL, LPC, TFRI
	F2.5-XS	16	24	43	4,0	880	2,1	460									
	F2	16	19	34	2,0	440	1,0	220									
Ultra	F1.5	16	14	25	1,0	220	0,5	110									

** Tested in a Test fixture: c=0,5

* in Progress

More details and other temperature ranges are available on request